

FSCAN Food Inspection System 9500D(H)

X-ray Automatic Vision Inspection System



Company: Dong Phuong Hn

Date: 25 Oct. 2022

Quotation No: XQ221025-1

Quoted by Charlie Park

Email: chpark@xavis.co.kr

Tel: +82-31-740-3842


Mobile +82-10-3135-6788

XAVIS


FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

General system overview



- X-rays are connected to the production-line by the conveyor belt.
- X-ray beaming to the detector and image analysis enables to detect the presence of any contaminant in the product.
- Any irregularity of X-ray machine can be diagnosed by Xavis using remote connection through USB internet or WI-FI. – Real time service



<Online support program>

FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

Why X-ray inspection system?



- **Data management**

Provides reports on defective and good products inspected by X-ray. Reports can be categorized into annual, monthly, weekly and daily reports and saved as an Excel file.



- **Image management**

Save all produced images for post-tracking management

- **Data analysis**

Information on production and operation of the product can be seen on a various type of chart.


Model	Start Date	Start Time	End Date	End Time	OK	NG	FO/LN
Test	2018.10.11	10:40:05	2018.10.11	10:40:13	0	5	5
Test	2018.10.11	10:40:33	2018.10.11	10:41:41	0	3	3
Test	2018.10.11	10:41:48	2018.10.11	10:42:05	0	3	3
Test	2018.10.11	10:42:36	2018.10.11	10:43:43	0	29	29
Test	2018.10.08	14:41:15	2018.10.08	14:41:31	0	7	7
Test	2018.10.08	14:41:37	2018.10.08	14:42:30	0	6	6
Test	2018.10.08	14:48:19	2018.10.08	14:48:20	0	1	1
Test	2018.10.08	11:55:44	2018.10.08	11:55:52	0	4	4
Test	2018.10.08	11:58:01	2018.10.08	11:58:09	0	2	2
Test	2018.10.08	10:20:41	2018.10.08	10:21:13	0	14	14
Test	2018.10.08	10:28:31	2018.10.08	10:28:33	0	1	1
Test	2018.10.08	10:28:39	2018.10.08	10:28:54	0	2	2
Test	2018.10.08	10:28:52	2018.10.08	10:28:53	0	5	5
Test	2018.10.08	09:55:48	2018.10.08	09:55:57	0	5	5
Test	2018.09.29	10:51:00	2018.09.29	10:51:12	0	2	2
Test	2018.09.29	10:48:17	2018.09.29	10:48:40	0	6	6
Test	2018.09.29	10:47:36	2018.09.29	10:47:37	0	1	1
Test	2018.09.29	10:47:36	2018.09.29	10:47:37	0	1	1





FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

External Dimensions – 9500D(H)



Dectction area



FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

Protection class – 9500D(H)

- ※ Upper part
 - IP55 with cooling fan
 - IP65 with AC excluding vent of AC (AC: IP34)




- ※ Lower part(conveyor): IP66

FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

Automatic Reject (※ Optional)



Pusher type with roller

※ Additional Options

- Combination rejector (with reject confirmation function)
- Air conditioner
- Adjusting belt height (Maximum 900mm)
- Increasing belt speed
- Increasing tunnel height
- Lockable rejector bin

FSCAN Food Inspection System

X-ray Automatic Vision Inspection System

Specifications – 9500D(H)

X-ray tube	MAX. 120kV, 4.0mA, 480W	
Detector	Maximum detecting width	954 mm
	Maximum detecting height	460 mm
Conveyor	Speed	7.5 ~ 25 M/M
	Width	1,000 mm
	Maximum product weight	25 kg
Tower lamp	3 colors	
Control computer	Industrial computer	
Monitor	15"~17" Touch screen	
Interface	Possible to store at USB port	
Product register function	Possible to register max. 10,000 models of product	
Masking function	Image of product, function of image brightness (16 kinds)	
Product management	Daily/Month/Model product capacity analysis	
Equipment management	MTBF, MTTR, Error log, Error analysis	
Teaching	Auto teaching , Manual teaching	
Image management	Image Save/Analysis [Defect size measurement]	
Protection class	Conveyor in & out IP66 Body IP55 with cooling fan (IP65 with AC excluding vent of AC) (AC: IP34)	
Washing	Easy to clean	
X-ray leakage	Maximum 1 μ Sv/h or less	
Power requirements	AC220V, 50/60Hz, 1.5kVA	
Weight	Approx. 730 kg	
Temperature	0°C ~ 35°C	

- ※ All specifications are subject to change without prior notice
- ※ Sensitivity is dependent on the material as well as size and array of examined object
- ※ The height of belt level: 800±50mm (option for adjusting belt height, max. 900mm)
- ※ Options available for increasing belt speed, tunnel height and product weight